

# KAIA

## LIA

'Cutting through darkness'

Designed by Peter Straka  
Vienna 2005-07


LIA's three-flamed elegance captivates when on, yet this suspension light almost disappears into its surrounding when the lights are off.



Process: The brass is cut, bent in its shape and polished. Then all the components are nickel plated or the brass is brushed and painted with a clear lacquer to maintain the natural effect of the brass. Lastly all parts are assembled to the LIA lighting object.

### LIA

Suspension  
100




Type	Suspension light
Material	Brass
Environment	Indoors
Dimension	1000 x 125 mm - 39.37 x 4.92 "
Cable Length	Standard mounting 1500mm - 59.06 "
Weight	2.1 kg - 4.63 lb
Certification	IP20 CE; ETL US/CSA Canada
EU/UK - US	230 V - 110 V
Ceiling Rose	Ø 80 x 25 mm - Ø 3.15 x 0.98"; flat Ø 100 mm - Ø 3.94"
Lamps	max 3 x 120 W, S14s, our suggestion: 3x linear opal LED, 2700 K, 1055 lm, Mains (Phase) dimmable, EPREL-ID: 566195
Lamps US	3x Linear opal LED S14s*, 13W, 2700K, 1150 lm, Mains dimmable (leading edge)
Standard finishes:	
050 01 201 12	brushed nickel, black cable
050 01 202 12	brushed brass, black cable
050 01 209 12	black matte, black cable
050 01 101 11	polished nickel, transparent cable

On very rare occasions, these lamps may appear to have a slight buzzing or flickering. As is the case with all retro LED lamps, this is likely caused by a number of outside influences such as incorrect installation, wiring, dimming or transformers and in some instances low electrical resistance.

Please contact [sales@kaialighting.com](mailto:sales@kaialighting.com) for further information on dimmers etc. Please note KAIA Ltd cannot take any responsibility for the connection with your dimming or central control system. It is the customer's responsibility to ensure the compatibility with their systems.

**LIA**  
Suspension  
50




Type	Suspension light
Material	Brass
Environment	Indoors
Dimension	500 x 125 mm - 19.69 x 4.92 "
Cable Length	Standard mounting 1500 mm - 59.06 "
Weight	1.9 kg - 4.19 lb
Certification	IP20 CE; ETL US/CSA Canada
EU/UK - US	230 V - 110 V
Ceiling Rose	Ø 80 x 25 mm - Ø 3.15 x 0.98 "; flat Ø 100 mm - Ø 3.94 "
Lamps	max. 3 x 60 W, S14s, our suggestion: 3x linear opal LED, 2700 K, 470 lm, Mains (Phase) dimmable, EPREL-ID: 566200
Lamps US	3x Linear opal LED S14s*, 7W, 2700K, 610 lm, Mains dimmable (leading edge)

Standard finishes:

050 02 201 12	brushed nickel, black cable
050 02 202 12	brushed brass, black cable
050 02 209 12	black matte, black cable
050 02 101 11	polished nickel, transparent cable

**LIA**  
Suspension  
30




Type	Suspension light
Material	Brass
Environment	Indoors
Dimension	300 x 125 mm - 11.81 x 4.92 "
Cable Length	Standard mounting 1500 mm - 59.06 "
Weight	1.8 kg - 3.97 lb
Certification	IP20 CE; ETL US/CSA Canada
EU/UK - US	230 V - 110 V
Ceiling Rose	Ø 80 x 25 mm - Ø 3.15 x 0.98 "; flat Ø 100 mm - Ø 3.94 "
Lamps	our suggestion: 3 x linear opal LED, 2700 K, 275 lm, Mains (Phase) dimmable, EPREL-ID: 566198
Lamps US	Glass lamps not available. Please inquire.

Standard finishes:

050 03 201 12	brushed nickel, black cable
050 03 202 12	brushed brass, black cable
050 03 209 12	black matte, black cable
050 03 101 11	polished nickel, transparent cable

**LIA**  
Suspension  
Diagonal



Type	Suspension light
Material	Brass
Environment	Indoors
Dimension	1000/500/300 mm - 39.37 / 19.69 / 11.81 "
Cable Length	Standard mounting 1500 mm- 59.06 " Max. 2000 mm - 78.74 "
Weight	2.1 kg - 4.63 lb
Certification	IP20 CE; ETL US/CSA Canada
EU/UK - US	230 V - 110 V
Ceiling Rose	Ø 80 x 25 mm - Ø 3.15 x 0.98 "
Lamps	max 3 x 120 W, S14s, our suggestion: 3x linear opal LED, 2700 K, 1055 lm, Mains (Phase) dimmable, EPREL-ID: 566195
Lamps US	see LIA Suspension 100/50/30 specifications

Standard finishes:

100/50/30	
050 04/09/10 201 12	brushed nickel, black cable
050 04/09/10 202 12	brushed brass, black cable
050 04/09/10 209 12	black matte, black cable
050 04/09/10 101 11	polished nickel, transparent cable

