


w224 Alto pendant traffic white



Technical information

Physical

Material Canopy, rod & lamp body: aluminium

Optics Reflector: polycarbonate Cover: glass

IP rating 20

Protection class I

LED

Light source COB LED (included)

Lifetime expectancy L80 / 50,000 h

CRI Colour rendering index ≥ 90

Standard deviation of colour matching 3-step MacAdam

Replaceable by a professional

The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The applicable General Terms & Conditions apply.

Article-specific information

Version

Mounting

LED Colour temperature (CCT) / Luminous flux

Voltage / System power

Efficacy

Light control

Net weight

Packaging dimensions

Gross weight

s1 / s1 r: 2700 K (CCT) / 1.2 m rod

Traffic white (RAL 9016)

Jet black (RAL 9005)

Raw tumbled

s1 / s1 r: 2700 K (CCT) / 2.5 m rod

Traffic white (RAL 9016)

Jet black (RAL 9005)

Raw tumbled

s1 / s1 r: 3000 K (CCT) / 1.2 m rod

Traffic white (RAL 9016)

Jet black (RAL 9005)

Raw tumbled

s1 / s1 r: 3000 K (CCT) / 2.5 m rod

Traffic white (RAL 9016)


Jet black (RAL 9005)

Raw tumbled

Accessories

Casambi module

w224 Alto pendant s1



s1

Ceiling suspended

2700 K / 10350 lm
3000 K / 10790 lm

220–240 V / 91 W

118 lm / W

DALI dim-Push dim

2.7 kg / 2.7 kg

L23.4 × W22 × H18.4cm / L23.4 × W22 × H18.4cm

3.4 kg / 3.4 kg

Art. No. / EAN code

224S102272 / 7330492002637

224S105272 / 7330492002644

Art. No. / EAN code

224S1202272 / 7330492002675

224S1205272 / 7330492002682

Art. No. / EAN code

224S102302 / 7330492002217

224S105302 / 7330492002224

Art. No. / EAN code


224S1202302 / 7330492002651

224S1205302 / 7330492002668

Art. No. / EAN code

DR-0601 / 7330492000510

w224 Alto pendant s1 r



Article-specific information

Version	s1 r
Mounting	Ceiling suspended
LED Colour temperature (CCT) / Luminous flux	2700 K / 10350 lm 3000 K / 10790 lm
Voltage / System power	220–240 V / 91 W
Efficacy	118 lm / W
Light control	DALI dim-Push dim
Net weight	2.7 kg / 2.7 kg
Packaging dimensions	L23.4 × W22 × H18.4cm / L23.4 × W22 × H18.4cm
Gross weight	3.4 kg / 3.4 kg

s1 / s1 r: 2700 K (CCT) / 1.2 m rod

	Art. No. / EAN code
Traffic white (RAL 9016)	224S1R02272 / 7330492002712
Jet black (RAL 9005)	224S1R05272 / 7330492002705
Raw tumbled	224S11R20272 / 7330492002712

s1 / s1 r: 2700 K (CCT) / 2.5 m rod

	Art. No. / EAN code
Traffic white (RAL 9016)	224S2R02272 / 7330492002774
Jet black (RAL 9005)	224S2R05272 / 7330492002767
Raw tumbled	224S12R20272 / 7330492002774

s1 / s1 r: 3000 K (CCT) / 1.2 m rod

	Art. No. / EAN code
Traffic white (RAL 9016)	224S1R02302 / 7330492002729
Jet black (RAL 9005)	224S1R05302 / 7330492002736
Raw tumbled	224S11R20302 / 7330492002743

s1 / s1 r: 3000 K (CCT) / 2.5 m rod

	Art. No. / EAN code
Traffic white (RAL 9016)	224S2R02302 / 7330492002781
Jet black (RAL 9005)	224S2R05302 / 7330492002798
Raw tumbled	224S12R20302 / 7330492002804

Accessories

Casambi module

Art. No. / EAN code