




w225 lon 3000 K narrow



w225 lon 3000 K wide



w225 lon b4040



Technical information

Physical

Material	Lamp body & wall bracket: aluminium Base & pin: steel
-----------------	--

Optics	Glare shade: polyamide Lens: polycarbonate
---------------	---

IP rating	20
------------------	----

Protection class	III
-------------------------	-----

LED

Light source	COB LED (included)
---------------------	--------------------

Lifetime expectancy	L80 / 50,000 h
----------------------------	----------------

CRI Colour rendering index	97
-----------------------------------	----

Standard deviation of colour matching	3-step MacAdam
--	----------------

Replaceable by a professional

The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The applicable General Terms & Conditions apply.

Article-specific information

Version

Mounting

LED Colour temperature (CCT) / Luminous flux

Voltage / System power

Efficacy

Beam angle / Optics

Light control

Net weight

Packaging dimensions

Gross weight

2700 K Colour temperature (CCT)

Traffic white (RAL 9016)

Jet black (RAL 9005)

Raw tumbled

3000 K Colour temperature (CCT)

Traffic white (RAL 9016)

Jet black (RAL 9005)

Raw tumbled

Accessories

Adapter suitable for USM Haller Table

Adapter suitable for USM Haller Shelf

Adapter suitable for Vitra Joyn 2

Adapter suitable for Vitra Tyde 2

Narrow / Lens

Wide / Reflector & diffuser

Packaging dimensions

b4040

Base

3000 K / 439 lm

100–240 V / 6.3 W

60 lm / W

Wide / Lens

Dimmable

3.3 kg

L58.3 × W31.6 × H10.1 cm

4.9 kg

Art. No. / EAN code

Art. No. / EAN code

225B40400230W / 7330492000541

225B40400530W / 7330492000558

225B40402030W / 7330492001845

Art. No. / EAN code


225-N01

L64.8 x W31.6 x H10.1 cm (0.02 m³)

w225 lon p4040



w225 lon b9040



Article-specific information

Version	p4040	b9040
Mounting	Pin - integrated (hole $\varnothing 14$ mm)	Floor base
LED Colour temperature (CCT) / Luminous flux	3000 K / 439 lm	2700 K / 380 lm 3000 K / 405 lm
Voltage / System power	100–240 V / 6.3 W	100–240 V / 6.3 W
Efficacy	60 lm / W	70 lm / W
Beam angle / Optics	Wide / Lens	Narrow / Lens
Light control	Dimmable	Dimmable
Net weight	0.48 kg	3.3 kg
Packaging dimensions	L58.3 × W31.6 × H10.1 cm	L104.4 × W36.3 × H10.1 cm
Gross weight	2.1 kg	6.8 kg

2700 K Colour temperature (CCT)

Traffic white (RAL 9016)	<input type="radio"/>
Jet black (RAL 9005)	<input checked="" type="radio"/>
Raw tumbled	<input type="radio"/>

Art. No. / EAN code

Art. No. / EAN code

225B90400227N / 7330492000602
225B90400527N / 7330492000619

3000 K Colour temperature (CCT)

Traffic white (RAL 9016)	<input type="radio"/>
Jet black (RAL 9005)	<input checked="" type="radio"/>
Raw tumbled	<input type="radio"/>

Art. No. / EAN code

225P40400230W / 7330492000565
225P40400530W / 7330492000572
225P40402030W / 7330492001852

Art. No. / EAN code

225B90400230N / 7330492000589
225B90400530N / 7330492000596

Accessories

Adapter suitable for USM Haller Table	<input type="checkbox"/>
Adapter suitable for USM Haller Shelf	<input type="checkbox"/>
Adapter suitable for Vitra Joyn 2	<input type="checkbox"/>
Adapter suitable for Vitra Tyde 2	<input type="checkbox"/>
Narrow / Lens	<input type="checkbox"/>
Wide / Reflector & diffuser	<input type="checkbox"/>
Packaging dimensions	<input type="checkbox"/>


Art. No. / EAN code

225ACC001 / 7330492002002
225ACC006 / 7330492002019
225ACC002 / 7330492002026
225ACC003 / 7330492002033
225-N01

Art. No. / EAN code

225-W01

w225 lon br4040



w225 lon br0



Article-specific information

Version	br4040	br0
Mounting	Wall bracket	Wall bracket
LED Colour temperature (CCT) / Luminous flux	3000 K / 439 lm	2700 K / 380 lm 3000 K / 405 lm
Voltage / System power	100–240 V / 6.3 W	100–240 V / 6.3 W
Efficacy	60 lm / W	70 lm / W
Beam angle / Optics	Wide / Lens	Narrow / Lens
Light control	Dimmable	Dimmable
Net weight	0.5 kg	0.4 kg
Packaging dimensions	L58.3 × W31.6 × H10.1 cm	L15.4 × W14.3 × H13.1 cm
Gross weight	2.2 kg	0.6 kg

2700 K Colour temperature (CCT)

Traffic white (RAL 9016)	<input type="radio"/>
Jet black (RAL 9005)	<input checked="" type="radio"/>
Raw tumbled	<input type="radio"/>

Art. No. / EAN code

Art. No. / EAN code

	225BR00227N / 7330492000664
	225BR00527N / 7330492000671
	225BR02027N / 7330492001906

3000 K Colour temperature (CCT)

Traffic white (RAL 9016)	<input type="radio"/>
Jet black (RAL 9005)	<input checked="" type="radio"/>
Raw tumbled	<input type="radio"/>

Art. No. / EAN code

	225BR40400230W / 7330492000626
	225BR40400530W / 7330492000633
	225BR40402030W / 7330492001883

Art. No. / EAN code

	225BR00230N / 7330492000640
	225BR00530N / 7330492000657
	225BR02030N / 7330492001890

Accessories

Adapter suitable for USM Haller Table	
Adapter suitable for USM Haller Shelf	
Adapter suitable for Vitra Joyn 2	
Adapter suitable for Vitra Tyde 2	
Narrow / Lens	225-N01
Wide / Reflector & diffuser	

Art. No. / EAN code

Art. No. / EAN code

	225-W01